



### Benefits

- ▶ Our strongest and most powerful 1" impact with an extended anvil
- ▶ Operator productivity
- ▶ Convenient reverse valve for ease of use
- ▶ Ideal for high volume tire work on trucks, buses, and heavy equipment



### Features

- ▶ 1" impact wrench
- ▶ Rocking dog clutch
- ▶ 4-position power settings throttle for ease of use
- ▶ Convenient reverse valve
- ▶ Plus 7" extended anvil

<b>Technical description</b>		
<b>Part number</b>	T024585	
<b>Model</b>	CP5000	
<b>Handle type</b>	D-Handle Inside Trigger	
<b>Square drive</b>	1"	
<b>Working Torque Range (fwd)</b>	240-2,800 Nm	185-2,065
<b>Maximum Torque (reverse)</b>	3390 Nm	2500 ft.lbs
<b>Free speed</b>	3700 rpm	
<b>Blows per minute</b>	540	
<b>Net weight</b>	16.2 kg	35.71 lb
<b>Power/weight ratio</b>	209.3 Nm/kg	70 ft.lb/lb
<b>Length</b>	572 mm	22.5"
<b>Average air consumption</b>	5.6 l/s	11.88 cfm
<b>Actual air consumption</b>	25 l/s	52 cfm
<b>Air inlet thread size</b>	0.5 "	
<b>Min. hose size</b>	13 mm	1/2"
<b>Sound pressure</b>	103 db(A)	

<b>Sound Power</b>	114 db(A)
<b>Vibration (ISO-8662-7)</b>	8.9 m/s <sup>2</sup>
<b>Vibration <math>\alpha</math> (ISO-28927-2)</b>	8.5 m/s <sup>2</sup>
<b>Vibration K (ISO-28927-2)</b>	2.6 m/s <sup>2</sup>
<b>Socket retainer</b>	Dual (hole+friction)
<b>Clutch type</b>	Pinless rocking dog
<b>Box dimensions</b>	680x240x170