



Ratio 1:1
Capacity 23lt/min



Air - operated transfer pump 23 lt/min

Suitable for transferring various low viscosity (density) fluids such as hydraulic fluid, oil, waste oil, anti freeze and allied products at short and medium distances.

These range of pumps are equipped with special **TEFLON SEALS**

Royal recommends applying delivery hoses of min 1/2" optimal 3/4".

WARNING:
Do not use flammable or corrosive fluids.

	R011	R027	R074	R094
Compression ratio	1 : 1	1 : 1	1 : 1	1 : 1
Air inlet connection	F 1 / 4"G	F 1 / 4"G	F 1 / 4"G	F 1 / 4"G
Oil outlet connection	F 1 / 2"G	F 1 / 2"G	F 1 / 2"G	F 1 / 2"G
Working pressure	6 - 8 bar	6 - 8 bar	6 - 8 bar	6 - 8 bar
Max. pressure	8 bar	8 bar	8 bar	8 bar
Air consumption	230 lt/min	230 lt/min	230 lt/min	230 lt/min
Relative capacity (free delivery at 6 bar)	23 lt/min	23 lt/min	23 lt/min	23 lt/min
Noise level	81 dB	81 dB	81 dB	81 dB
Temperature oil delivered	-10 + 50°C	-10 + 50°C	-10 + 50°C	-10 + 50°C
Max. viscosity oil delivered	80 SAE	80 SAE	80 SAE	80 SAE
Suitable for drums of	-	-	50 - 60 kg	180 - 220 kg
Weight	3 kg	3,8 kg	4,7 kg	5 kg
Suction tube length	-	-	740	940
Suction tube diameter	wall - mounted	42 mm	42 mm	42 mm